

MESSAGE NO: 9153115

MESSAGE DATE: 06/02/1999

MESSAGE STATUS: Active

CATEGORY: Antidumping

TYPE: FIN-Final Determination

PUBLIC ☒

NON-PUBLIC ☐

SUB-TYPE:

FR CITE: FR

FR CITE DATE:

REFERENCE
MESSAGE #
(s):

CASE #(s): A-588-846

EFFECTIVE DATE:

COURT CASE #:

PERIOD OF REVIEW:

TO

PERIOD COVERED: 05/06/1999 TO

Notice of Lifting of Suspension Date:

TO: { Directors Of Field Operations, Port Directors }

FROM: { Director AD/CVD & Revenue Policy & Programs }

RE: NOTICE OF A FINAL DETERMINATION IN AN ANTIDUMPING DUTY INVESTIGATION
OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON QUALITY STEEL PRODUCTS FROM
JAPAN (A-588-846)

MESSAGE NO: 9153115

DATE: 06 02 1999

CATEGORY: ADA

TYPE: FIN

REFERENCE:

REFERENCE DATE:

CASES: A - 588 - 846

- -

- -

- -

- -

- -

PERIOD COVERED: 05 06 1999 TO

LIQ SUSPENSION DATE:

TO: DIRECTORS OF FIELD OPERATIONS

PORT DIRECTORS

FROM: DIRECTOR, IMPORT OPERATIONS

RE: NOTICE OF A FINAL DETERMINATION IN AN ANTIDUMPING DUTY
INVESTIGATION OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON
QUALITY STEEL PRODUCTS FROM JAPAN (A-588-846)

1. ON MAY 6, 1999, THE DEPARTMENT OF COMMERCE PUBLISHED IN THE
FEDERAL REGISTER ITS FINAL DETERMINATION OF SALES AT LESS
THAN FAIR VALUE IN THE ANTIDUMPING DUTY INVESTIGATION OF
CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL PRODUCTS
FROM JAPAN.
2. FOR PURPOSES OF THIS INVESTIGATION, THE PRODUCTS COVERED ARE
CERTAIN HOT-ROLLED FLAT-ROLLED CARBON- QUALITY STEEL

PRODUCTS OF A RECTANGULAR SHAPE, OF A WIDTH OF 0.5 INCH OR GREATER, NEITHER CLAD, PLATED, NOR COATED WITH METAL AND WHETHER OR NOT PAINTED, VARNISHED, OR COATED WITH PLASTICS OR OTHER NON-METALLIC SUBSTANCES, IN COILS (WHETHER OR NOT IN SUCCESSIVELY SUPERIMPOSED LAYERS) REGARDLESS OF THICKNESS, AND IN STRAIGHT LENGTHS, OF A THICKNESS LESS THAN 4.75 MM AND OF A WIDTH MEASURING AT LEAST 10 TIMES THE THICKNESS. UNIVERSAL MILL PLATE (I.E., FLAT-ROLLED PRODUCTS ROLLED ON FOUR FACES OR IN A CLOSED BOX PASS, OF A WIDTH EXCEEDING 150 MM BUT NOT EXCEEDING 1250 MM AND OF A THICKNESS OF NOT LESS THAN 4 MM, NOT IN COILS AND WITHOUT PATTERNS IN RELIEF) OF A THICKNESS NOT LESS THAN 4.0 MM IS NOT INCLUDED WITHIN THE SCOPE OF THESE INVESTIGATIONS.

SPECIFICALLY INCLUDED IN THIS SCOPE ARE VACUUM DEGASSED, FULLY STABILIZED (COMMONLY REFERRED TO AS INTERSTITIAL-FREE ("IF")) STEELS, HIGH STRENGTH LOW ALLOY ("HSLA") STEELS, AND THE SUBSTRATE FOR MOTOR LAMINATION STEELS. IF STEELS ARE RECOGNIZED AS LOW CARBON STEELS WITH MICRO-ALLOYING LEVELS OF ELEMENTS SUCH AS TITANIUM AND/OR NIOBIUM ADDED TO STABILIZE CARBON AND NITROGEN ELEMENTS. HSLA STEELS ARE RECOGNIZED AS STEELS WITH MICRO-ALLOYING LEVELS OF ELEMENTS SUCH AS CHROMIUM, COPPER, NIOBIUM, TITANIUM, VANADIUM, AND MOLYBDENUM. THE SUBSTRATE FOR MOTOR LAMINATION STEELS CONTAINS MICRO-ALLOYING LEVELS OF ELEMENTS SUCH AS SILICON AND ALUMINUM.

STEEL PRODUCTS TO BE INCLUDED IN THE SCOPE OF THIS INVESTIGATION, REGARDLESS OF HTSUS DEFINITIONS, ARE PRODUCTS IN WHICH: 1) IRON PREDOMINATES, BY WEIGHT, OVER EACH OF THE OTHER CONTAINED ELEMENTS; 2) THE CARBON CONTENT IS 2 PERCENT OR LESS, BY WEIGHT; AND 3) NONE OF THE ELEMENTS LISTED BELOW EXCEEDS THE QUANTITY, BY WEIGHT, RESPECTIVELY INDICATED:

1.80 PERCENT OF MANGANESE, OR

1.50 PERCENT OF SILICON, OR

1.00 PERCENT OF COPPER, OR

0.50 PERCENT OF ALUMINUM, OR

1.25 PERCENT OF CHROMIUM, OR

0.30 PERCENT OF COBALT, OR
0.40 PERCENT OF LEAD, OR
1.25 PERCENT OF NICKEL, OR
0.30 PERCENT OF TUNGSTEN, OR
0.012 PERCENT OF BORON, OR
0.10 PERCENT OF MOLYBDENUM, OR
0.10 PERCENT OF NIOBIUM, OR
0.41 PERCENT OF TITANIUM, OR
0.15 PERCENT OF VANADIUM, OR
0.15 PERCENT OF ZIRCONIUM.

ALL PRODUCTS THAT MEET THE PHYSICAL AND CHEMICAL DESCRIPTION PROVIDED ABOVE ARE WITHIN THE SCOPE OF THIS INVESTIGATION UNLESS OTHERWISE EXCLUDED. THE FOLLOWING PRODUCTS, BY WAY OF EXAMPLE, ARE OUTSIDE AND/OR SPECIFICALLY EXCLUDED FROM THE SCOPE OF THIS INVESTIGATION:

ALLOY HOT-ROLLED STEEL PRODUCTS IN WHICH AT LEAST ONE OF THE CHEMICAL ELEMENTS EXCEEDS THOSE LISTED ABOVE (INCLUDING E.G., ASTM SPECIFICATIONS A543, A387, A514, A517, AND A506).

SAE/AISI GRADES OF SERIES 2300 AND HIGHER.

BALL BEARING STEELS, AS DEFINED IN THE HTSUS.

TOOL STEELS, AS DEFINED IN THE HTSUS.

SILICO-MANGANESE (AS DEFINED IN THE HTSUS) OR SILICON ELECTRICAL STEEL WITH A SILICON LEVEL EXCEEDING 1.50 PERCENT.

ASTM SPECIFICATIONS A710 AND A736.

USS ABRASION-RESISTANT STEELS (USS AR 400, USS AR 500).

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.10 - 0.14%

MN 0.90% MAX

P 0.025% MAX

S 0.005% MAX

SI 0.30 - 0.50%

CR 0.50 - 0.70%

CU 0.20 - 0.40%

NI 0.20% MAX

WIDTH

44.80 INCHES MAXIMUM; THICKNESS

0.063 - 0.198

INCHES;

YIELD STRENGTH

50,000 KSI MINIMUM; TENSILE STRENGTH

70,000 - 88,000 PSI.

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING
CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.10 - 0.16%

MN 0.70 - 0.90%

P 0.025% MAX

S 0.006% MAX

SI 0.30 - 0.50%

CR 0.50 - 0.70%

CU 0.25% MAX

NI 0.20% MAX

MO 0.21% MAX

WIDTH

44.80 INCHES MAXIMUM; THICKNESS

0.350 INCHES

MAXIMUM;

YIELD STRENGTH

80,000 KSI MINIMUM; TENSILE STRENGTH

105,000 PSI AIM.

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING
CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.10 - 0.14%

MN 1.30 - 1.80%

P 0.025% MAX

S 0.005% MAX

SI 0.30 - 0.50%

CR 0.50 - 0.70%

CU 0.20 - 0.40%

NI 0.20% MAX
V(WT.) 0.10 MAX
CB 0.08% MAX

WIDTH

44.80 INCHES MAXIMUM; THICKNESS

0.350 INCHES

MAXIMUM;

YIELD STRENGTH

80,000 KSI MINIMUM; TENSILE STRENGTH

105,000 PSI AIM.

HOT-ROLLED STEEL COIL WHICH MEETS THE FOLLOWING
CHEMICAL, PHYSICAL AND MECHANICAL SPECIFICATIONS:

C 0.15% MAX
MN 1.40% MAX
P 0.025% MAX
S 0.010% MAX
SI 0.50% MAX
CR 1.00% MAX
CU 0.50% MAX
NI 0.20% MAX
NB 0.005% MIN
CA TREATED
AL 0.01 - 0.07%

WIDTH

39.37 INCHES; THICKNESS

0.181 INCHES MAXIMUM;

YIELD STRENGTH

70,000 PSI MINIMUM FOR THICKNESSES

0.148 INCHES AND 65,000 PSI MINIMUM FOR THICKNESSES

>0.148 INCHES; TENSILE STRENGTH

80,000 PSI MINIMUM.

HOT-ROLLED DUAL PHASE STEEL, PHASE-HARDENED, PRIMARILY
WITH A FERRITIC-MARTENSITIC MICROSTRUCTURE, CONTAINS
0.9 PERCENT UP TO AND INCLUDING 1.5 PERCENT SILICON BY
WEIGHT, FURTHER CHARACTERIZED BY EITHER (I) TENSILE

STRENGTH BETWEEN 540 N/MM AND 640 N/MM AND AN ELONGATION PERCENTAGE 26 PERCENT FOR THICKNESSES OF 2 MM AND ABOVE, OR (II) A TENSILE STRENGTH BETWEEN 590 N/MM AND 690 N/MM AND AN ELONGATION PERCENTAGE 25 PERCENT FOR THICKNESSES OF 2MM AND ABOVE.

HOT-ROLLED BEARING QUALITY STEEL, SAE GRADE 1050, IN COILS, WITH AN INCLUSION RATING OF 1.0 MAXIMUM PER ASTM E 45, METHOD A, WITH EXCELLENT SURFACE QUALITY AND CHEMISTRY RESTRICTIONS AS FOLLOWS: 0.012 PERCENT MAXIMUM PHOSPHORUS, 0.015 PERCENT MAXIMUM SULFUR, AND 0.20 PERCENT MAXIMUM RESIDUALS INCLUDING 0.15 PERCENT MAXIMUM CHROMIUM.

GRADE ASTM-A570-50 HOT-ROLLED STEEL SHEET IN COILS OR CUT LENGTHS, WIDTH OF 74 INCHES (NOMINAL, WITHIN ASTM TOLERANCES), THICKNESS OF 11 GAUGE (0.119 INCH NOMINAL), MILL EDGE AND SKIN PASSED, WITH MINIMUM COPPER CONTENT OF 0.20 PERCENT.

THE MERCHANDISE SUBJECT TO THESE INVESTIGATIONS IS CLASSIFIED IN THE HARMONIZED TARIFF SCHEDULE OF THE UNITED STATES ("HTSUS") AT SUBHEADINGS: 7208.10.15.00, 7208.10.30.00, 7208.10.60.00, 7208.25.30.00, 7208.25.60.00, 7208.26.00.30, 7208.26.00.60, 7208.27.00.30, 7208.27.00.60, 7208.36.00.30, 7208.36.00.60, 7208.37.00.30, 7208.37.00.60, 7208.38.00.15, 7208.38.00.30, 7208.38.00.90, 7208.39.00.15, 7208.39.00.30, 7208.39.00.90, 7208.40.60.30, 7208.40.60.60, 7208.53.00.00, 7208.54.00.00, 7208.90.00.00, 7210.70.30.00, 7210.90.90.00, 7211.14.00.30, 7211.14.00.90, 7211.19.15.00, 7211.19.20.00, 7211.19.30.00, 7211.19.45.00, 7211.19.60.00, 7211.19.75.30, 7211.19.75.60, 7211.19.75.90, 7212.40.10.00, 7212.40.50.00, 7212.50.00.00. CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL COVERED BY THIS INVESTIGATION, INCLUDING: VACUUM DEGASSED, FULLY STABILIZED; HIGH STRENGTH LOW ALLOY; AND THE SUBSTRATE FOR MOTOR LAMINATION STEEL MAY ALSO ENTER UNDER THE FOLLOWING TARIFF NUMBERS:

7225.11.00.00, 7225.19.00.00, 7225.30.30.50, 7225.30.70.00, 7225.40.70.00, 7225.99.00.90, 7226.11.10.00, 7226.11.90.30, 7226.11.90.60, 7226.19.10.00, 7226.19.90.00, 7226.91.50.00,

7226.91.70.00, 7226.91.80.00, AND 7226.99.00.00. ALTHOUGH THE HTSUS SUBHEADINGS ARE PROVIDED FOR CONVENIENCE AND CUSTOMS PURPOSES, THE WRITTEN DESCRIPTION OF THE MERCHANDISE UNDER INVESTIGATION IS DISPOSITIVE.

3. FOR IMPORTS OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL PRODUCTS FROM JAPAN, THE CUSTOMS SERVICE SHALL SUSPEND LIQUIDATIONS OF UNLIQUIDATED ENTRIES OF SUBJECT MERCHANDISE ENTERED, OR WITHDRAWN FROM WAREHOUSE, FOR CONSUMPTION ON OR AFTER NOVEMBER 21, 1998, (90 DAYS PRIOR TO THE PRELIMINARY DETERMINATION, DUE TO THE DEPARTMENT'S FINAL DETERMINATION OF CRITICAL CIRCUMSTANCES) FOR KAWASAKI STEEL COMPANY, AND THOSE COMPANIES WHICH FALL UNDER THE "ALL-OTHERS" CATEGORY. EFFECTIVE MAY 6, 1999, CUSTOMS SHALL REQUIRE, FOR SUCH ENTRIES, A CASH DEPOSIT OR BOND EQUAL TO THE MARGINS SHOWN BELOW:

MFR/PRODUCER/ EXPORTER	CUSTOMS ID NUMBER	MARGIN/ AD VALOREM PERCENTAGE
KAWASAKI STEEL CORPORATION	A-588-846-002	67.14
ALL OTHERS	A-588-846-000	29.30

4. FOR IMPORTS OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL PRODUCTS FROM JAPAN, THE CUSTOMS SERVICE SHALL SUSPEND LIQUIDATIONS OF UNLIQUIDATED ENTRIES OF SUBJECT MERCHANDISE ENTERED OR WITHDRAWN FROM WAREHOUSE, FOR CONSUMPTION ON OR AFTER FEBRUARY 19, 1999 (THE DATE OF THE DEPARTMENT'S PRELIMINARY DETERMINATION) FOR NIPPON STEEL CORPORATION, AND NKK CORPORATION. EFFECTIVE MAY 6, 1999, CUSTOMS SHALL REQUIRE, FOR SUCH ENTRIES, A CASH DEPOSIT OR BOND EQUAL TO THE MARGINS SHOWN BELOW:

MFR/PRODUCER/ EXPORTER	CUSTOMS ID NUMBER	MARGIN/ AD VALOREM PERCENTAGE
---------------------------	----------------------	-------------------------------------

NIPPON STEEL CORPORATION A-588-846-003 19.65

NKK CORPORATION A-588-846-001 17.86

5. ALSO FOR NIPPON STEEL CORPORATION AND NKK CORPORATION, CUSTOMS SHALL REFUND CASH DEPOSITS AND RELEASE BONDS FOR ENTRIES OF CERTAIN HOT-ROLLED FLAT-ROLLED CARBON-QUALITY STEEL PRODUCTS FROM JAPAN ENTERED, OR WITHDRAWN FROM WAREHOUSE, FOR CONSUMPTION BEFORE FEBRUARY 19, 1999 (I.E., THE CRITICAL CIRCUMSTANCES PERIOD). THESE ENTRIES SHOULD BE LIQUIDATED WITHOUT REGARD TO ANTIDUMPING DUTIES.
6. IF THERE ARE ANY QUESTIONS REGARDING THIS MATTER BY CUSTOMS OFFICERS, PLEASE CONTACT, VIA E-MAIL, THROUGH THE APPROPRIATE SUPERVISORY CHANNELS, OTHER GOVERNMENT AGENCY LIAISON, USING THE ATTRIBUTE "HQ OAB." THE IMPORTING PUBLIC AND OTHER INTERESTED PARTIES SHOULD CONTACT NITHYA NAGARAJAN , OFFICE OF AD/CVD ENFORCEMENT, IMPORT ADMINISTRATION, INTERNATIONAL TRADE ADMINISTRATION, U.S. DEPARTMENT OF COMMERCE, AT (202) 482-4243.
7. THERE ARE NO RESTRICTIONS ON THE RELEASE OF THIS INFORMATION.

PAUL SCHWARTZ

Company Details

*Party Indicator Value:

I = Importer, M = Manufacturer, E = Exporter, S = Sold To Party